

# SAFETY DATA SHEET

Issue Date 4/6/16 Revision Date 11/04/2019 Version 1

# 1. IDENTIFICATION

Product identifier

Product Name: Alpha Syn L.E. Plus Engine Oil 15w40

Other means of identification

**Product code:** F-421 **Synonyms:** None

Recommended use of the chemical and restrictions on use

Recommended Use: Lubricant.

Uses advised against: No information available

Details of the supplier of the safety data sheet

Supplier Address

FRONTIER PERFORMANCE LUBRICANTS INC

PO BOX 1777 LODI, CA 95241 Phone: (800)-807-4496 Fax: (209)-334-6408

**Emergency telephone number** 

**Emergency Telephone:** PERS (800)-633-8253

## 2. HAZARDS IDENTIFICATION

Classification of the Mixture Most Important Hazards Liquid, Slight petroleum odor.

This material is considered hazardous by the OSHA Hazard Communication Standard (29

CFR 1910.1200).

Hazard Category Acute Oral Toxicity Category 4

Skin Irritation Category 2
Eye Irritation Category 2A
Skin Sensitization Category 1B

Signal Word Warning!

Pictogram



**Hazard Statements** Causes serious eye irritation.

Causes skin sensitization with susceptible individuals. Causes eye, skin and respiratory tract irritation.

Harmful if swallowed.

**Precautionary Statements** 

Prevention Avoid breathing dust/fume/gas/mist/vapors/spray. Use only with adequate ventilation. Do not eat,

drink or smoke when using this product Wash thoroughly after handling.

Response Contaminated work clothing must not be allowed out of the workplace. Wash contaminated

clothing before reuse. If in eyes, rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention

If on skin: wash with plenty of water.

If swallowed, call a poison center/doctor if you feel unwell

Storage Keep container tightly closed. Store locked up

**Disposal** Dispose of contents/containers in accordance with local and national regulations.

Carcinogenicity:

IARC No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible, or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible, or confirmed human carcinogen by OSHA.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible, or confirmed human carcinogen by NTP

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

IngredientWT %CAS #Distillates, hydrotreated heavy paraffinic65-8564742-54-7Zinc alkyl dithiophosphate<1</td>84605-29-8

To the knowledge of the supplier, there are no other ingredients in this product that are classified as hazardous.

## 4. FIRST AID MEASURES

Eyes Flush eyes with running water for at least 15 minutes. If redness, burning, blurred vision or

irritation persists, transport to nearest medical facility for additional treatment.

**Skin** Flush skin with water, wash with soap and water. If irritation occurs, get medical attention.

Remove contaminated clothing. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

**Ingestion** Do NOT induce vomiting and obtain medical attention. Have victim rinse mouth out with water. If

vomiting occurs spontaneously, keep head below hips to prevent aspiration.

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim

has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give oxygen

with rescue breathing or CPR as required and transport to the nearest medical facility.

#### 5. FIRE-FIGHTING MEASURES

Flammable Properties

Base Oil Flash point >210°C (ASTM D92)

Flammable limits in air N/A
Auto ignition temperature N/A

Extinguishing media

Special firefighting measure

CO<sub>2</sub>, dry chemical, foam, alcohol-resistant foam, water mist

Procedures for an oil fire should be utilized. Use self-contained breathing apparatus. Use foam or dry chemical to extinguish fire. Water may be used <u>only</u> to keep surrounding containers cool. Firefighters should wear proper protective equipment and self-contained breathing apparatus

with full face piece operated in positive pressure mode.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions/Procedures: Use PPE and ensure adequate ventilation.

**Environmental Precautions:** Should not be released into the environment.

Do not contaminate water.

Do not flush to surface water or sanitary sewer system.

Methods and Materials for Containment/Clean Up:

Contain spillage, soak up with non-combustible absorbent material (e.g. sand, earth,

diatomaceous earth, vermiculite) and transfer to a container for disposal according to

local/national regulations (see section 13).

#### 7. HANDLING AND STORAGE

Handling and Storage Precautions Avoid heat, open flames, including pilot lights, and strong oxidizing agents. Use explosion-proof ventilation to prevent vapor accumulation. Ground all handling equipment to prevent sparking.

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Have appropriate fire extinguishers and spill clean-up equipment

in or near storage area.

**Respiratory Protection** 

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls**Use adequate ventilation to keep vapors and mists of this material below applicable standards.

Recommended work place control parameters - based on mineral oil ACGIH TWA 5 mg/m<sup>3</sup>. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and

maintenance should be in accordance with the requirements of the OSHA Respiratory Protection

Standard, 29 CFR 1910.134.

**Skin Protection**Use protective clothing that is chemically resistant to this product. Acceptable materials for

gloves and aprons are: neoprene, nitrile rubber or viton.

**Eye Protection** Use safety glasses or goggles. Have suitable eye wash water available.

Other/General Protection For mists and vapors: Air purifying, organic vapor cartridge, NIOSH approved respirator. Use

self-contained breathing apparatus for environments with unknown concentrations or emergency

situations.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Amber/Brown	Vapor Pressure:	N/A	Solubility in Water:	Insoluble
Appearance:	Liquid	% Volatile by Volume:	N/A	Evaporation Rate	N/A
Odor:	Characteristic	Vapor Density (air = 1):	N/A	(Butyl Acetate = 1):	<1
<b>Boiling Point:</b>	N/A	Reactivity in Water:	Non-reactive	Specific Gravity:	0.80-0.91

#### 10. STABILITY AND REACTIVITY

Stability Stable

Conditions to avoid Sources of ignition.

IncompatibilityStrong oxidizing or reducing agents.Decomposition ProductsOxides of Carbon and Hydrogen.

Hazardous Polymerization Will not occur.

## 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

**Potential Health Effects** 

Inhalation, skin, eyes and ingestion.

**Eye Effects** Can cause irritation, redness, burns, and tissue destruction.

**Skin Effects** Can cause inflammation, and significant irritation.

Oral Effects Gastrointestinal tract irritation, nausea, and vomiting if swallowed.

**Inhalation Effects** May cause respiratory tract irritation.

Chronic Health Effects

No data available to indicate product or components present in mixture are chronic health

hazards.

Mutagenicity Negative
Carcinogenicity None anticipated

Reproductive Effects
Teratogenicity
Sensitization
Negative.
Negative.
See section 2

**Toxicological Data** ATE oral is >2,000 mg/kg

ATE dermal is > 4,000 mg/kg

ATE inhalation (mist/aerosol) is estimated at 2.2 mg/L/4 h

## 12. ECOLOGICAL INFORMATION

Not classified due to inadequate data available on this mixture. Highly recommend avoidance of release to the environment.

# 13. DISPOSAL CONSIDERATIONS

Avoid release to the environment. Dispose in a safe manner in accordance with national, state and local regulations. Not a RCRA hazardous waste if uncontaminated. If "used" RCRA criteria must be determined. Dispose of container by recycling or if permitted incineration.

# 14. TRANSPORT INFORMATION

Proper Shipping Name PETROLEUM LUBRICATING OIL; NOT REGULATED AS A HAZARDOUS MATERIAL FOR

TRANSPORTATION UNDER 49 CFR.

Shipping Class

#### Alpha Syn L.E. Plus Engine Oil 15w40

Dot Identification Number N/A

**Dot Shipping Label** Not regulated by DOT.

**TDG Classification** Not controlled under TDG (Canada).

# 15. REGULATORY INFORMATION

**U.S. Federal Regulatory Information** 

SARA 302 Threshold Planning Quantity
SARA 304 Reportable Quantity

N/A

SARA 311 Categories

Acute Health Effects

Chronic Health Effects

None
Fire Hazard

No
Sudden Release of Pressure Hazard

No
Reactivity Hazard

No

EPA/TSCA Inventory Listed

EPA Hazard Classification Code Not applicable

CERCLA No components are subject to reporting.

SARA Title III - Section 313 Supplier Notification

No Chemicals in this product exceed the DE Minimus reporting level established by SARA Title

III, Section 313 and 40 CFR 372.

WHMIS Classification
Other Regulations
WHMIS controlled. Class D; Division 2, Subdivision B: otherwise causing toxic effects.
All components of this formulation are listed on the CEPA-DSL (Domestic Substance List)

# **16. OTHER INFORMATION**

#### **NFPA Hazard Rating:**

Health:	1	Slight
Flammability:	1	Slight
Reactivity:	0	Negligible

<sup>\*</sup>Threshold Limit Value/Personal Exposure Limit

N/A = Not Applicable N/E = Not Established

 Issue Date
 4/6/16

 Revision Date
 11/04/2019

 Revision Note
 Not applicable

# **Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**